


## For tension tests ≤ 500 N

	<b>Long clamp</b> for tension and rupture tests up to 500 N, clamping width: 3 mm, thread: M6	<b>AC 17R</b> 1 piece <b>AC 17</b>
		2 pieces
	<b>Angle bracket</b> for tension and rupture tests up to 500 N (e.g. for cable tests), clamping width: 22 mm, thread: M6	<b>AC 01R</b> 1 piece <b>AC 01</b>
		2 pieces
	<b>Rope and thread clamp</b> for tension and rupture tests up to 500 N thread: M6	<b>AC 10S*</b> 1 piece
	<b>Fine point clamp</b> for tension and rupture tests up to 500 N, width 15 mm, clamping width: 4 mm, thread: M6	<b>AC 14R</b> 1 piece <b>AC 14</b>
		2 pieces
	<b>Fine point clamp</b> for tension and rupture tests up to 500 N, width 22 mm, clamping width: 4 mm, thread: M6	<b>AC 22R</b> 1 piece <b>AC 22</b>
		2 pieces
	<b>Screw tension clamp</b> for 100 N for laboratory tensile force measurements, incl. jaws with pyramid grip, clamping width: 4 mm, thread: M6 Further jaws on request	<b>AD 9001</b> 1 piece 
	<b>Screw tension clamp</b> for 400 N for laboratory tensile force measurements, incl. jaws with pyramid grip <b>1</b> with adapter structure for AD-system, <b>2</b> with M6 thread, clamping width: 8 mm Further jaws on request	<b>AD 9005</b> 1 piece 

## For tension tests ≤ 5000 N

	<b>Flat jaw attachment</b> for tension tests up to 5 kN (e.g. textile, paper etc.), clamping width: 4 mm, thread: M6	<b>AC 03R</b> 1 piece <b>AC 03</b>
		2 pieces
	<b>Parallel jaw grip</b> for tension and rupture tests up to 5 kN, clamping width: 5 mm, thread: M10	<b>AC 12R</b> 1 piece <b>AC 12</b>
		2 pieces
	<b>High capacity small clamp</b> for tension and rupture tests up to 5 kN, clamping width: 5 mm, thread: M10	<b>AC 16R*</b> 1 piece <b>AC 16*</b>
		2 pieces
	<b>2 wide jaw grip attachment</b> for tension and extraction tests up to 5 kN, jaw width 60 mm, clamping width: 33 mm, thread: M10	<b>AC 18R</b> 1 piece <b>AC 18</b>
		2 pieces
	<b>Rolling-clamp attachment</b> for tension and rupture tests up to 5 kN, thread: M10	<b>AC 11R</b> 1 piece
	<b>1-jaw-clamp attachment</b> for tension and rupture tests up to 5 kN, clamping width: 3 mm, thread: M6	<b>AC 13R*</b> 1 piece <b>AC 13*</b>
		2 pieces
	<b>Eccentric roll clamp</b> in particular for cable tests up to 5 kN, 10×30 mm slotted hole, clamping width: 9 mm	<b>AC 41*</b> 1 piece
	<b>Drum clamp</b> typically for cable connector extraction tests up to 5 kN, for test objects with ∅ from 1,5 mm up to 8 mm, thread: M10	<b>AC 42*</b> 1 piece
	<b>Wedge tension clamp</b> up to 5 kN, for tensile force tests, due to the wedge shape of the clamp the specimen is clamped automatically with increasing load, clamping width up to 10 mm, jaws with pyramid grip	<b>AD 9080</b> 1 piece 
	<b>Rope and thread tension clamp</b> up to 1 kN, Suitable for wires up to a diameter of 2 mm, belts up to 7 mm width, incl. jaws with rubberised surface	<b>AD 9120</b> 1 piece 

 \*ONLY WHILE STOCKS LAST

**For tension tests ≤ 5000 N**



**Rope and thread tension clamp** AD 9121  
 up to 5 kN, for clamping belts, ropes, wires, etc.  
 Suitable for wires up to a diameter of 5 mm, belts up to 8 mm. jaws with pyramid grip  
 1 piece  
 PREMIUM  
 ★★★



**Roller tension clamp** AD 9205  
 up to 1 kN, can clamp on one side and eccentrically. suitable for tensile force tests with belts or any other soft, flexible, flat material with a maximum sample thickness of 7 mm, incl. rollers with pyramid grip, the opposite clamping surface is smooth.  
 Suitable for test objects up to 50 mm width  
 1 piece  
 PREMIUM  
 ★★★



**Roller tension clamp** AD 9207  
 up to 5 kN, can clamp on one side and eccentrically. Suitable for tensile force tests with belts or any other soft, flexible, flat material with a maximum sample thickness of 7 mm, incl. rollers with pyramid grip, the opposite clamping surface is smooth.  
 Suitable for test objects up to 50 mm width  
 1 piece  
 PREMIUM  
 ★★★

**For tension tests > 5000 N**



**Belt tension clamp** AD 9250  
 up to 10 kN, open at one end, suitable for tensile force tests with belts or any other soft, flexible, flat materials with a maximum sample thickness of 2,5 mm a test object width up to 22 mm  
 1 piece  
 PREMIUM  
 ★★★



**Belt tension clamp** AD 9255  
 up to 20 kN, suitable for tensile force tests with belts or any other soft, flexible, flat materials with a maximum sample thickness of 2,5 mm a test object width up to 80 mm  
 1 piece  
 PREMIUM  
 ★★★



**Wedge tension clamp** AD 9090  
 up to 10kN, for tensile force tests, due to the wedge shape of the clamp the specimen is clamped automatically with increasing load, clamping width up to 10 mm, incl. jaws with pyramid grip  
 Further jaws on request  
 PREMIUM  
 ★★★ NEW



**Wedge tension clamp** AD 9095  
 up to 20kN, for tensile force tests, due to the wedge shape of the clamp the specimen is clamped automatically with increasing load, clamping width up to 13 mm, incl. jaws with pyramid grip  
 Further jaws on request  
 PREMIUM  
 ★★★ NEW



**Wedge tension clamp** AD 9096  
 up to 50kN, for tensile force tests, due to the wedge shape of the clamp the specimen is clamped automatically with increasing load, clamping width up to 13 mm, incl. jaws with pyramid grip  
 Further jaws on request  
 PREMIUM  
 ★★★ NEW

## For compression tests > 500 N

	<b>Concave force sensor</b> with optimised radius for the measurement particularly of arms and legs up to 1 kN, thread: M6	<b>AC 45</b>  1 piece
	<b>Flat square-shaped sensor</b> for lateral power sensing of back, chest or arm up to 1 kN, thread: M6	<b>AC 46</b>  1 piece
	<b>Round sensor</b> to measure particular muscle groups, such as, for example, the shoulder up to 1 kN, inner thread: M6	<b>AC 47</b>  1 piece
	<b>Pressure disc</b> out of aluminium, thickness 10 mm, for compression tests up to 5 kN, diam. 110 mm, outer thread: M12	<b>AFH 06</b>  1 piece
	<b>Pressure disc</b> for compression tests up to 5 kN (e. g. plastics), $\phi$ 49 mm, inner thread: M10	<b>AC 08R*</b>  1 piece <b>AC 08*</b>  2 pieces
	<b>Ball-shaped head made of nickel-plated steel</b> for compression and fracture tests up to 5 kN, (e.g. foam, glass), thread: M6/M10 Ball radius: 5mm/8mm	<b>AC 02</b>  1 piece each
	<b>Small 3-point bending device (steel)</b> up to 10 kN, central scale 80-0-80 mm. Consisting of one support beam, two support brackets and a curved fin each with permanently fixed radii, radii on request. Gap between the two support brackets 4-170 mm. Width of the brackets 30 mm	<b>AD 9300</b>  1 piece  

## For tension and compression tests

	<b>Threaded adapters</b> made of steel for SAUTER force measuring devices, clamps and test stands, external thread 1: M6 external thread 2: M12	<b>AFM 14</b>  1 piece  
	<b>Threaded adapters</b> made of steel, for SAUTER force gauges, clamps and test stands, external thread: M10 internal thread: M6	<b>AFM 05</b>  1 piece  
	<b>Threaded adapters</b> made of steel, for SAUTER force gauges, clamps and test stands, external thread: M12 internal thread: M10	<b>AFM 16</b>  1 piece  
	<b>Threaded adapters</b> made of steel for SAUTER force gauges and clamps, external thread: M6 internal thread: M8	<b>AFM 22</b>  1 piece  
	<b>Threaded adapters</b> made of steel, for SAUTER force gauges, clamps and test stands, external thread: M10 internal thread: M6	<b>AFM 07</b>  1 piece  
	<b>Grub screw</b> made of steel for SAUTER clamps and test stands, external thread: M6	<b>AFM 20</b>  1 piece  
	<b>Threaded adapters</b> made of steel, for SAUTER force gauges, clamps and test stands, external thread: M10 internal thread: M8	<b>AFM 23</b>  1 piece  

Numerous more adapters can be found at the Internet

\*ONLY WHILE STOCKS LAST

**For tension tests ≤ 500 N**



**Standard small clamp** **AE 01**  
 Opening width (inside the jaws):  
 0-7 mm, for tensile tests up to 500 N,  
 thread M6. Overload protection: 150 %  
 of [Max]. **PREMIUM** **★★★**  
 1 piece  
 Easy handling without tools, the opening  
 and closing of the jaws can be made  
 with the rotary knob on the upper side.  
 Presetting of the jaw opening via attached  
 screws. Pretension due to built-in springs



**Wide jaw clamp** **AE 02**  
 Opening width (inside the jaws):  
 0-6 mm, for tensile tests up to 500 N,  
 thread M6. Overload protection: 150 %  
 of [Max]. **PREMIUM** **★★★**  
 1 piece  
 Easy handling without tools, the opening  
 and closing of the jaws can be made  
 with the rotary knobs on the upper side



**Belt tension clamps** **AE 03**  
 Opening width (inside the jaws):  
 0-4 mm, for tensile tests up to 500 N,  
 thread M6. Overload protection: 150 %  
 of [Max]. **PREMIUM** **★★★**  
 1 piece  
 Easy handling without tools, the opening  
 and closing of the jaws can be made  
 with the lever on the upper side



**Belt tension clamps** **AE 04**  
 Opening width (inside the jaws):  
 0-6 mm, for tensile tests up to 500 N,  
 thread M6. Overload protection: 150 %  
 of [Max]. **PREMIUM** **★★★**  
 1 piece  
 Easy handling without tools, the opening  
 and closing of the jaws can be made  
 with the lever on the upper side



**Rope and thread tension clamps** **AE 05**  
 Opening width (inside the jaws):  
 0-5 mm, for tensile tests up to 500 N,  
 thread M6. Overload protection: 150 %  
 of [Max]. **PREMIUM** **★★★**  
 1 piece  
 Easy handling without tools, test item  
 can simply be wrapped around the screw  
 and fastened via the clamping screw

**For tension tests ≤ 500 N**



**Cable removal clamp** **AE 06**  
 Opening width (inside the jaws):  
 1,5-6 mm, for tensile tests up to 500 N,  
 thread M6. Overload protection: 150 %  
 of [Max]. **PREMIUM** **★★★**  
 1 piece  
 Easy handling without tools, test item  
 can simply be inserted into the appropri-  
 ate recess and be tested



**Wedge tension clamp** **AE 07**  
 Opening width (inside the jaws):  
 0-6 mm, for tensile tests up to 500 N,  
 thread M6. Overload protection: 150 %  
 of [Max]. **PREMIUM** **★★★**  
 1 piece  
 Easy handling without tools, test item  
 can simply be inserted into the open  
 clamp. It closes automatically during a  
 tensile test

**For compression tests ≤ 5000 N**



**Stainless steel pressure disc** **AE 08**  
 For compression tests up to 5 kN,  
 ø 47 mm, internal thread M6, foam  
 rubber attachment for sensitive  
 surfaces included in scope of delivery  
**PREMIUM** **★★★** **NEW**  
 1 piece

## Attachments

	<b>Standard attachments kit</b> for all force gauges FA, FH, FL, FC and FS, thread: M6 10-500 N	<b>AC 43</b> 6 items
--	--	-------------------------

	<b>Standard attachments kit</b> for force gauge FK, thread: M8 10-1000 N	<b>AC 430</b> 6 items
--	---	--------------------------

	<b>Tensiometer attachment</b> optional for all FK models from FK 10 up to FK 250	<b>FK-A01</b> 1 piece
--	---	--------------------------

	<b>Tensiometer attachment</b> for high-capacity tensile strength tests up to FK 500 and FK 1K	<b>FK-A02</b> 1 piece
--	--	--------------------------

## Special solutions

	<b>Stainless steel handle bar</b> with rubber grip for safe handling, AFH 04 suitable for FA, FH, FL	<b>AFH 04</b> 1 piece
	AFK 02 suitable for FK, FC and FS	<b>AFK 02</b> 1 piece

	<b>Stainless steel handle bar</b> with rubber grip for FH, FL with external sensor, thread: M12	<b>AFH 05</b> 1 piece
--	--	--------------------------

	<b>Door tester</b> Handle (length: 300 mm) and two round force receptor plates (ø 85 mm) as an option to FH 1K up to FH 5K for the safe testing of clamping forces (not approved to DIN 18650 or similar), up to 5 kN	<b>AFH 03</b> 1 piece
--	--	--------------------------

## Interface cables

	<b>RS-232/PC connection cable</b> to connect models from the SAUTER FH range to a PC	<b>FH-A01</b> 1 piece
--	---	--------------------------

	<b>RS-232/PC connection cable</b> to connect models from the SAUTER FL, DA and DB range to a PC	<b>FL-A04</b> 1 piece
--	--	--------------------------

	<b>USB/PC connection cable</b> to connect models from the SAUTER FL, DA and DB range to a PC	<b>FL-A01</b> 1 piece
--	---	--------------------------

	<b>RS-232/PC connection cable</b> to connect models from the SAUTER LB range to a PC	<b>LB-A01</b> 1 piece
--	---	--------------------------

	<b>RS-232/USB adapter</b> to connect peripheral devices with USB interface, suitable for all balances and measuring instruments with RS 232 output, scope of supply: adapter, CD with driver	<b>AFH 12</b> 1 piece
--	---	--------------------------

	<b>RS-232 connection cable</b> to connect models from the SAUTER FC	<b>FC-A01</b> 1 piece
--	--	--------------------------



**Adjusting program (CAL):**  
For quick setting of the instrument's accuracy. External adjusting weight required



**Calibration block:**  
Standard for adjusting or correcting the measuring device



**Peak hold function:**  
Capturing a peak value within a measuring process



**Scan mode:**  
Continuous capture and display of measurements



**Push and Pull:**  
The measuring device can capture tension and compression forces



**Length measurement:**  
Captures the geometric dimensions of a test object or the movement during a test process



**Focus function:**  
Increases the measuring accuracy of a device within a defined measuring range



**Internal memory:**  
To save measurements in the device memory



**Data interface RS-232:**  
Bidirectional, for connection of printer and PC



**Profibus:**  
For transmitting data, e.g. between scales, measuring cells, controllers and peripheral devices over long distances. Suitable for safe, fast, fault-tolerant data transmission. Less susceptible to magnetic interference.



**Profinet:**  
Enables efficient data exchange between decentralised peripheral devices (balances, measuring cells, measuring instruments etc.) and a control unit (controller). Especially advantageous when exchanging complex measured values, device, diagnostic and process information. Savings potential through shorter commissioning times and device integration possible



**Data interface USB:**  
To connect the measuring instrument to a printer, PC or other peripheral devices



**Bluetooth\* data interface:**  
To transfer data from the balance/measuring instrument to a printer, PC or other peripherals



**WLAN data interface:**  
To transfer data from the balance/measuring instrument to a printer, PC or other peripherals



**Data interface Infrared:**  
To transfer data from the measuring instrument to a printer, PC or other peripheral devices



**Control outputs (optocoupler, digital I/O):**  
To connect relays, signal lamps, valves, etc.



**Analogue interface:**  
To connect a suitable peripheral device for analogue processing of the measurements



**Analog output:**  
For output of an electrical signal depending on the load (e.g. voltage 0 V - 10 V or current 4 mA - 20 mA)



**Statistics:**  
Using the saved values, the device calculates statistical data, such as average value, standard deviation etc.



**PC Software:**  
To transfer the measurement data from the device to a PC



**Printer:**  
A printer can be connected to the device to print out the measurement data



**Network interface:**  
For connecting the scale/measuring instrument to an Ethernet network



**KERN Communication Protocol (KCP):**  
It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems



**GLP/ISO record keeping:**  
Of measurement data with date, time and serial number. Only with SAUTER printers



**Measuring units:**  
Weighing units can be switched to e.g. non-metric. Please refer to website for more details



**Measuring with tolerance range (limit-setting function):**  
Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model



**Protection against dust and water splashes IPxx:**  
The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013



**ZERO:**  
Resets the display to "0"



**Battery operation:**  
Ready for battery operation. The battery type is specified for each device



**Rechargeable battery pack:**  
Rechargeable set



**Plug-in power supply:**  
230V/50Hz in standard version for EU. On request GB, AUS or USA version available



**Integrated power supply unit:**  
Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request



**Motorised drive:**  
The mechanical movement is carried out by an electric motor



**Motorised drive:**  
The mechanical movement is carried out by a synchronous motor (stepper)



**Fast-Move:**  
The total length of travel can be covered by a single lever movement



**Verification possible:**  
Models with type approval for construction of verifiable systems



**DAkKS calibration possible:**  
The time required for DAkKS calibration is shown in days in the pictogram



**Factory calibration:**  
The time required for factory calibration is specified in the pictogram



**Package shipment:**  
The time required for internal shipping preparations is shown in days in the pictogram



**Pallet shipment:**  
The time required for internal shipping preparations is shown in days in the pictogram

\*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.