


## Compact Laboratory Balance KERN EWJ



## High-quality precision balance with automatic internal adjustment, verification optional

### Features

- **NEW:** EWJ 600-3/EWJ 6000-2: The measuring system's exceptionally high resolution of 600.000 points ensures the highest level of accuracy with large weighing ranges
- **NEW:** Weighing with tolerance range (check-weighing): a visual and audible signal helps with portioning, dispensing or grading
- Standardised, convenient KERN concept of operation: All primary functions have their own key on the keypad
- Automatic internal adjustment, time-controlled every 2 h, guarantees high degree of accuracy and makes the balance independent of its location
- Capacity display: A bargraph display lights up to show how much of the weighing range is still available

- KERN EWJ/-H/-M: USB data interface for transferring weighing data to the PC, printer etc.
- Small draught shield as standard for models with weighing plate size **A**, **B**, removable, Weighing space W×D×H 134×128×80 mm
- **I** KERN EWJ 300-3H/EWJ 600-3: Large glass draught shield with 3 sliding doors for easy access to the items being weighed. Weighing space W×D×H 155×175×217 mm
- Protective working cover included with delivery


### Technical data

- Large LCD display, digit height 21 mm
- Dimensions weighing surface, stainless steel
  - A** Ø 80 mm
  - B** Ø 120 mm
  - C** Ø 135 mm, see larger picture
  - D** W×D 155×145 mm
- Permissible ambient temperature  
KERN EWJ: 15 °C/35 °C  
KERN EWJ-M: 15 °C/30 °C

### Accessories

- Protective working cover, scope of delivery 5 items, KERN EWJ-A04S05
- Internal rechargeable battery pack, operating time up to 57 h without backlight, charging time approx. 6,5 h, KERN EWJ-A06
- KERN EWJ/-H/-M: Software BalanceConnection, for flexible recording or transmission of measured values, in particular also to Microsoft® Excel or Access as well as transfer of this data to other Apps and programs, for more details see internet, scope of supplies: 1 CD, 1 license, KERN SCD-4.0
- Further details, plenty of further accessories and suitable printers see *Accessories*

### STANDARD



### OPTION



### FACTORY



Model	Weighing capacity [Max] g	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Linearity g	Overall dimensions W×D×H mm	Weighing plate	Options	
								Verification	DAkks Calibr. Certificate
<b>KERN</b>								<b>M II</b>	<b>DAkks</b>
								KERN	KERN
<b>EWJ 300-3H</b>	300	0,001	-	-	± 0,005	220×340×321	<b>A</b>	-	963-127
<b>EWJ 300-3</b>	300	0,001	-	-	± 0,005	220×340×90	<b>A</b>	-	963-127
<b>EWJ 600-3</b> <small>NEW</small>	600	0,001	-	-	± 0,005	220×340×321	<b>B</b>	-	963-103
<b>EWJ 3000-2</b>	3000	0,01	-	-	± 0,05	220×340×105	<b>C</b>	-	963-127
<b>EWJ 6000-2</b> <small>NEW</small>	6000	0,01	-	-	± 0,05	220×340×105	<b>D</b>	-	963-104
Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.									
<b>EWJ 600-2M</b>	600	0,01	0,1	0,5	± 0,03	220×340×90	<b>B</b>	965-216	963-127
<b>EWJ 6000-1M</b>	6000	0,1	1	5	± 0,3	220×340×105	<b>D</b>	965-217	963-128
Variants without data interfaces									
<b>EWJ 600-2SM</b>	600	0,01	0,1	0,5	± 0,03	220×340×90	<b>B</b>	965-216	963-127
<b>EWJ 6000-1SM</b>	6000	0,1	1	5	± 0,3	220×340×105	<b>D</b>	965-217	963-128

NEW New model

**Internal adjusting**  
Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)

**Adjusting program CAL**  
For quick setting up of the balance's accuracy. External adjusting weight required

**EasyTouch**  
Suitable for the connection, data transmission and control through PC or tablet

**Memory**  
Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.

**Alibi memory**  
Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.

**KERN Universal Port (KUP)**  
allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WIFI, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort

**RS-232 Data interface**  
To connect the balance to a printer, PC or network

**RS-485 Data interface**  
To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible

**USB Data interface**  
To connect the balance to a printer, PC or other peripherals

**Bluetooth\* Data interface**  
To transfer data from the balance to a printer, PC or other peripherals

**WIFI Data interface**  
To transfer data from the balance to a printer, PC or other peripherals

**Control outputs**  
(optocoupler, digital I/O)  
To connect relays, signal lamps, valves, etc.

**Analogue interface**  
to connect a suitable peripheral device for analogue processing of the measurements

**Interface for second balance**  
For direct connection of a second balance

**Network interface**  
For connecting the scale to an Ethernet network

**KERN Communication Protocol (KCP)**  
It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems

**GLP/ISO log intern**  
The balance displays weight, date and time, independent of a printer connection

**GLP/ISO log Printer**  
With weight, date and time. Only with KERN printers.

**Piece counting**  
Reference quantities selectable. Display can be switched from piece to weight

**Recipe level A**  
The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out

**Recipe level B**  
Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display

**Totalising level A**  
The weights of similar items can be added together and the total can be printed out

**Percentage determination**  
Determining the deviation in % from the target value (100 %)

**Weighing units**  
Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details

**Weighing with tolerance range (Checkweighing)**  
Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model

**Hold function**  
(Animal weighing program)  
When the weighing conditions are unstable, a stable weight is calculated as an average value

**Protection against dust and water splashes IPxx**  
The type of protection is shown in the pictogram

**Suspended weighing**  
Load support with hook on the underside of the balance

**Battery operation**  
Ready for battery operation. The battery type is specified for each device

**Rechargeable battery pack**  
Rechargeable set

**Universal plug-in power supply**  
with universal input and optional input socket adapters for  
A) EU, CH, GB  
B) EU, CH, GB, US  
C) EU, CH, GB, US, AUS

**Plug-in power supply**  
230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available

**Integrated power supply unit**  
Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request

**Weighing principle Strain gauges**  
Electrical resistor on an elastic deforming body

**Weighing principle Tuning fork**  
A resonating body is electromagnetically excited, causing it to oscillate

**Weighing principle Electromagnetic force compensation**  
Coil inside a permanent magnet. For the most accurate weighings

**Weighing principle Single cell technology**  
Advanced version of the force compensation principle with the highest level of precision

**Conformity Assessment**  
The time required for conformity assessment is specified in the pictogram

**DAkkS calibration possible (DKD)**  
The time required for DAkkS calibration is shown in days in the pictogram

**Factory calibration (ISO)**  
The time required for Factory calibration is shown in days in the pictogram

**Package shipment**  
The time required for internal shipping preparations is shown in days in the pictogram

**Pallet shipment**  
The time required for internal shipping preparations is shown in days in the pictogram

\* The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.