

Display Devices KERN KFB-TM · KFS-TM



1 KERN KFB-TM

Display device with large digits – easy to read and optional analogue output for controlling systems (PLC) etc.

2 KERN KFS-TM




Professional indicator with 3 displays, also with EC type approval [M]

Tip

- to see what options are offered by this display device, please see the KERN platform scale IFB on page 114

Tip

- to see what options are offered by this display device, please see the KERN counting scale IFS on page 92



Features	Model KERN 1 KFB-TM	Model KERN 2 KERN KFS-TM
Display (segments)	5 + ½ digits	6 digits
EC type approval	yes	yes
Resolution verifiable	6000 e	3000 e
Resolution non verifiable	30000 d	60000 d
Weighing capacities	≤ 2	≤ 2
Weighing units	kg, lb	kg, g
Readability	1, 2, 5, 10, n	1, 2, 5, 10, n
Piece counting with reference	10, 20, 50, 100, 200	n
Display, digit height	Backlit LCD display, 52 mm	Backlit LCD displays, 13/16,5 mm
Additional functions	Totalising, HOLD function, Integrated KERN Communication Protocol (KCP), ideal for connecting an Merchandise Management or ERP system, Compatible with the KERN EasyTouch App	99 item memories, totalising, printing of date and time, Integrated KERN Communication Protocol (KCP), ideal for connecting an Merchandise Management or ERP system, Compatible with the KERN EasyTouch App
Strain gauge load cells	87 - 1600 Ω	87 - 1600 Ω
Linearisation	3 points	4 points
Input voltage	12 V, 500 mA	12 V, 500 mA
Permissible ambient temperature	-10 °C/40 °C	0 °C/40 °C
Interface RS-232	yes	yes
2. Interface RS-232, separate Y cable	CFS-A04	CFS-A04
Interface RS-485	-	-
Interface USB	-	-
Interface Bluetooth	KERN KFB-A03	-
Analogue module	0-10V: KERN KFB-A04 4-20 mA: KERN KFB-A05	-
Signal lamp	CFS-A03	CFS-A03
Foot switch	-	-
Stand	BFS-A07	BFS-A07
Benchtop stand for display device/wall mount	yes/yes	yes/yes
Protective working cover	KFB-A02S05,	KFB-A02S05,
Rechargeable battery pack	KFB-A01,	KFB-A01,
Operating/charging time	up to 35 h/12 h	up to 40 h/12 h
Dimensions Housing W×D×H	250×160×65 mm	260×150×65 mm
Net weight	1,2 kg	1,5 kg

* not possible in combination with verification. When installing the Bluetooth data interface, the RS-232 data interface can no longer be used

** not possible in combination with signal lamp. When installing the analogue module, the RS-232 data interface can no longer be used

Internal adjusting
Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)

Adjusting program CAL
For quick setting up of the balance's accuracy. External adjusting weight required

EasyTouch
Suitable for the connection, data transmission and control through PC or tablet

Memory
Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.

Alibi memory
Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.

KERN Universal Port (KUP)
allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WIFI, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort

RS-232 Data interface
To connect the balance to a printer, PC or network

RS-485 Data interface
To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible

USB Data interface
To connect the balance to a printer, PC or other peripherals

Bluetooth* Data interface
To transfer data from the balance to a printer, PC or other peripherals

WIFI Data interface
To transfer data from the balance to a printer, PC or other peripherals

Control outputs
(optocoupler, digital I/O)
To connect relays, signal lamps, valves, etc.

Analogue interface
to connect a suitable peripheral device for analogue processing of the measurements

Interface for second balance
For direct connection of a second balance

Network interface
For connecting the scale to an Ethernet network

KERN Communication Protocol (KCP)
It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems

GLP/ISO log intern
The balance displays weight, date and time, independent of a printer connection

GLP/ISO log Printer
With weight, date and time. Only with KERN printers.

Piece counting
Reference quantities selectable. Display can be switched from piece to weight

Recipe level A
The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out

Recipe level B
Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display

Totalising level A
The weights of similar items can be added together and the total can be printed out

Percentage determination
Determining the deviation in % from the target value (100 %)

Weighing units
Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details

Weighing with tolerance range (Checkweighing)
Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model

Hold function
(Animal weighing program)
When the weighing conditions are unstable, a stable weight is calculated as an average value

Protection against dust and water splashes IPxx
The type of protection is shown in the pictogram

Suspended weighing
Load support with hook on the underside of the balance

Battery operation
Ready for battery operation. The battery type is specified for each device

Rechargeable battery pack
Rechargeable set

Universal plug-in power supply
with universal input and optional input socket adapters for
A) EU, CH, GB
B) EU, CH, GB, US
C) EU, CH, GB, US, AUS

Plug-in power supply
230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available

Integrated power supply unit
Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request

Weighing principle Strain gauges
Electrical resistor on an elastic deforming body

Weighing principle Tuning fork
A resonating body is electromagnetically excited, causing it to oscillate

Weighing principle Electromagnetic force compensation
Coil inside a permanent magnet. For the most accurate weighings

Weighing principle Single cell technology
Advanced version of the force compensation principle with the highest level of precision

Conformity Assessment
The time required for conformity assessment is specified in the pictogram

DAkkS calibration possible (DKD)
The time required for DAkkS calibration is shown in days in the pictogram

Factory calibration (ISO)
The time required for Factory calibration is shown in days in the pictogram

Package shipment
The time required for internal shipping preparations is shown in days in the pictogram

Pallet shipment
The time required for internal shipping preparations is shown in days in the pictogram

* The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.