

Stereomicroscope Modular System – Heads KERN OZB-M



Head of the microscope series OZL-46
(OZL 461, 462)



Head of the microscope series OZM-5
(OZM 546, 547)



Head of the microscope series OZP-5
(OZP 551, 552)



Head of the microscope series OZO-5
(OZO 556, 557)

Individuality, variety and flexible working through our modular construction system ► Stereo microscope heads

Features

- To enable the highest level of flexibility for your special requirements and applications, we have a large selection of stereo microscope heads, universal stands and external illumination units, which are easy to combine
- Through the different properties of the stereo microscope heads, as well as the flexibility of the universal stands and the professional fixing of our brackets, we can configure your ideal microscope to suit your needs

- There are various microscope heads available from our product range for this purpose, both as binocular or trinocular versions
- A C-mount adapter is required to connect a camera to the trinocular version. You can select this adapter from the corresponding model outfit lists on the following pages

Technical data

- Optical system: Greenough optics
- Further technical data and model features is located in the tables below on the following pages
 - OZL-46: p. 76
 - OZM-5: p. 77
 - OZP-5: p. 78
 - OZO-5: p. 79

Model	Tube	Tube angle	Eyepieces (included)	Interpupillary distance	Objective	Magnification ratio	Diopter adjustment
					Zoom	Zoom	
OZL 516*	Binocular	45°	HSWF 10×/ø 23 mm	52–76 mm	2×/4×	-	One-sided (-6/6)
OZL 461	Binocular	45°	HWF 10×/ø 20 mm	55–75 mm	0,7× – 4,5×	6,4:1	Both-sided (-5/5)
OZL 462	Trinocular	45°	HWF 10×/ø 20 mm	52–76 mm	0,7× – 4,5×	6,4:1	Both-sided (-5/5)
OZM 546	Binocular	45°	HSWF 10×/ø 23 mm	52–76 mm	0,7× – 4,5×	6,4:1	Both-sided (-6/6)
OZM 547	Trinocular	45°	HSWF 10×/ø 23 mm	52–76 mm	0,7× – 4,5×	6,4:1	Both-sided (-6/6)
OZP 551	Binocular	35°	HSWF 10×/ø 23 mm	52–76 mm	0,6× – 5,5×	9,2:1	Both-sided (-6/6)
OZP 552	Trinocular	35°	HSWF 10×/ø 23 mm	52–76 mm	0,6× – 5,5×	9,2:1	Both-sided (-6/6)
OZO 556*	Binocular	35°	HSWF 10×/ø 23 mm	52–76 mm	0,8× – 7×	8,8:1	Both-sided (-6/6)

■ *ONLY WHILE STOCKS LAST

Fittings and accessories for the heads for microscope OSF-516

Eyepiece	Specifications - Objectives				
	Magnification	1×	2×	3×	4×
HSWF 10×	Total magnification	10×	20×	30×	40×
	Field of view mm	∅ 23	∅ 11,5	∅ 7,67	∅ 5,75
SWF 15×	Total magnification	15×	30×	45×	60×
	Field of view mm	∅ 17	∅ 8,5	∅ 5,67	∅ 4,25
SWF 20×	Total magnification	20×	40×	60×	80×
	Field of view mm	∅ 14	∅ 7	∅ 4,67	∅ 3,5
SWF 30×	Total magnification	30×	60×	90×	120×
	Field of view mm	∅ 9	∅ 4,5	∅ 3	∅ 2,25
Working distance		105 mm	105 mm	105 mm	105 mm

Model outfit	Model KERN		Order number
	OSF 516		
Eyepieces (30,0 mm)	HSWF 10×/∅ 23 mm	✓✓	OZB-A5503
	SWF 15×/∅ 17 mm	○ ○	OZB-A5504
	SWF 20×/∅ 14 mm	○ ○	OZB-A5505
	SWF 30×/∅ 9 mm	○ ○	OZB-A5506
	HSWF 10×/∅ 23 mm (reticule 0,1 mm)	○	OZB-A5512
	SWF 15×/∅ 17 mm (reticule 0,05 mm)	○	OZB-A5513
	SWF 20×/∅ 14 mm (reticule 0,05 mm)	○	OZB-A5514

✓ = Included with delivery ○ = Option

Fittings and accessories for the heads for the OZL-46 microscope range (OZL 461, OZL 462)

Eyepiece	Specifications - Objectives					
	Magnification	Standard	Auxiliary objectives			
		1,0×	0,5×	0,75×	1,5×	2,0×
HSWF 10×	Total magnification	7× - 45×	3,5× - 22,5×	5,3× - 33,8×	10,5× - 67,5×	14× - 90×
	Field of view mm	∅ 28,6 - 4,4	∅ 57,1 - 8,9	∅ 38,1 - 5,9	∅ 19 - 3	∅ 14,3 - 2,2
HWF 15×	Total magnification	10,5× - 67,5×	5,3× - 33,8×	7,9× - 50,6×	15,5× - 101,3×	21× - 135×
	Field of view mm	∅ 21,4 - 3,3	∅ 42,9 - 6,7	∅ 28,5 - 4,4	∅ 14,3 - 2,2	∅ 10,7 - 1,7
HSWF 20×	Total magnification	14× - 90×	7× - 45×	10,5× - 67,5×	21× - 135×	28× - 180×
	Field of view mm	∅ 14,3 - 2,2	∅ 28,6 - 4,4	∅ 19,1 - 2,9	∅ 9,5 - 1,5	∅ 7,1 - 1,1
HWF 25×	Total magnification	17,5× - 122,5×	8,8× - 56,3×	13,1× - 91,9×	26,3× - 168,8×	35× - 225×
	Field of view mm	∅ 12,9 - 2,0	∅ 25,7 - 4,0	∅ 17,2 - 2,7	∅ 8,6 - 1,3	∅ 6,4 - 1,0
Working distance		105 mm	177 mm	120 mm	47 mm	26 mm

Model outfit	Model KERN		Order number	
	OZL 461	OZL 462		
Eyepieces (30,0 mm)	HWF 10×/∅ 20 mm	✓✓	✓✓	OZB-A4631
	HSWF 15×/∅ 15 mm	○ ○	○ ○	OZB-A4632
	HWF 20×/∅ 10 mm	○ ○	○ ○	OZB-A4633
	HSWF 25×/∅ 9 mm	○ ○	○ ○	OZB-A4634
Auxiliary objectives	0,5×	○	○	OZB-A4641
	0,75×	○	○	OZB-A4644
	1,5×	○	○	OZB-A4642
	2,0×	○	○	OZB-A4643
C-Mount	1× (focus adjustable)		✓	OZB-A4809
	0,3× (focus adjustable)		○	OZB-A4810
	0,5× (focus adjustable)		○	OZB-A4811

✓ = Included with delivery ○ = Option

Fittings and accessories for the heads for the OZM-5 microscope range (OZM 546, OZM 547)

Eyepiece	Magnification	Specifications - Objectives						
		Standard	Auxiliary objectives					
			1,0×	0,37×	0,5×	0,7×	1,5×	2×
HSWF 10×	Total magnification	7× - 45×	2,59× - 16,65×	3,5× - 22,5×	4,9× - 31,5×	10,5× - 67,5×	14× - 90×	
	Field of view mm	∅ 32,8 - 5,1	∅ 88,8 - 13,8	∅ 65,7 - 10,2	∅ 46,9 - 7,3	∅ 21,9 - 3,4	∅ 16,4 - 2,6	
SWF 15×	Total magnification	10,5× - 67,5×	3,89× - 25×	5,3× - 33,8×	7,4× - 47,2×	15,8× - 101,3×	21× - 135×	
	Field of view mm	∅ 24,3 - 3,8	∅ 65,6 - 10,2	∅ 48,6 - 7,6	∅ 34,7 - 5,4	∅ 16,2 - 2,5	∅ 12,1 - 1,9	
SWF 20×	Total magnification	14× - 90×	5,18× - 33,3×	7× - 45×	9,8× - 63×	21× - 135×	28× - 180×	
	Field of view mm	∅ 20 - 3,1	∅ 54,1 - 8,4	∅ 40 - 6,2	∅ 28,6 - 4,4	∅ 13,3 - 2,1	∅ 10 - 1,6	
SWF 30×	Total magnification	21× - 135×	7,77× - 50×	10,5× - 67,5×	14,7× - 94,5×	31,5× - 202,5×	42× - 270×	
	Field of view mm	∅ 12,9 - 2	∅ 34,7 - 5,4	∅ 25,7 - 4	∅ 18,4 - 2,9	∅ 8,6 - 1,6	∅ 6,4 - 1	
Working distance		110 mm	275 mm	195 mm	145 mm	50 mm	35 mm	

Model outfit	Model KERN		Order number	
	OZM 546	OZM 547		
Eyepieces (30,0 mm)	HSWF 10×/∅ 23 mm	✓✓	✓✓	OZB-A5503
	SWF 15×/∅ 17 mm	○○	○○	OZB-A5504
	SWF 20×/∅ 14 mm	○○	○○	OZB-A5505
	SWF 30×/∅ 9 mm	○○	○○	OZB-A5506
	HSWF 10×/∅ 23 mm (reticule 0,1 mm)	○	○	OZB-A5512
	SWF 15×/∅ 17 mm (reticule 0,05 mm)	○	○	OZB-A5513
	SWF 20×/∅ 14 mm (reticule 0,05 mm)	○	○	OZB-A5514
Achromatic auxiliary objectives	0,37× only in combination with a universal stand	○	○	OZB-A5611
	0,5×	○	○	OZB-A5612
	0,7×	○	○	OZB-A5613
	1,5×	○	○	OZB-A5615
	2,0×	○	○	OZB-A5616
	Soldering protection lens	○	○	OZB-A5614
C-Mount	0,3× (focus adjustable)		○	OZB-A5701
	0,5× (focus adjustable)		○	OZB-A5702
	1,0× (focus adjustable)		○	OZB-A5703
	1,0× (with micrometer) only in combination with OZB-A5703		○	OZB-A5704
	For SLR cameras (Nikon)		○	OZB-A5706
	For SLR cameras (Olympus)		○	OZB-A5707
	For SLR cameras (Canon)		○	OZB-A5708

✓ = Included with delivery ○ = Option

Functionality of our Stereomicroscope Modular System

Step 1:

Select a microscope head (from page 78), a universal stand (page 80), a bracket (page 82) and a ring illumination unit (page 84), in order to generate a customised model.



Fittings and accessories for the heads for the OZP-5 microscope range (OZP 551, OZP 552)

Eyepiece	Magnification	Specifications - Objectives						
		Standard	Auxiliary objectives					
			1,0×	0,37×	0,5×	0,7×	1,5×	2×
HSWF 10×	Total magnification	6× - 55×	2,96× - 25,9×	3× - 27,5×	4,2× - 38,5×	9× - 82,5×	12× - 110×	
	Field of view mm	∅ 38,3 - 4,2	∅ 74,3 - 8,5	∅ 76,7 - 8,4	∅ 54,8 - 6	∅ 25,6 - 2,8	∅ 19,2 - 2,1	
SWF 15×	Total magnification	9× - 82,5×	4,44× - 38,9×	4,5× - 41,25×	6,3× - 57,75×	13,5× - 123,75×	18× - 165×	
	Field of view mm	∅ 28,3 - 3,1	∅ 57,4 - 6,6	∅ 56,7 - 6,2	∅ 40,5 - 4,4	∅ 18,9 - 2,1	∅ 14,2 - 1,5	
SWF 20×	Total magnification	12× - 110×	5,92× - 51,8×	6× - 55×	8,4× - 77×	18× - 165×	24× - 220×	
	Field of view mm	∅ 23,3 - 2,5	∅ 47,3 - 5,4	∅ 46,7 - 5,1	∅ 33,3 - 3,6	∅ 15,6 - 1,7	∅ 11,7 - 1,3	
SWF 30×	Total magnification	18× - 165×	8,88× - 77,7×	9× - 82,5×	12,6× - 115,5×	27× - 247,5×	36× - 330×	
	Field of view mm	∅ 15 - 1,6	∅ 30,4 - 3,5	∅ 30 - 3,3	∅ 21,4 - 2,3	∅ 10 - 1,1	∅ 7,5 - 0,8	
Working distance		108 mm	275 mm	195 mm	145 mm	50 mm	35 mm	

Model outfit	Model KERN		Order number	
	OZP 551	OZP 552		
Eyepieces (30,0 mm)	HSWF 10×/∅ 23 mm	✓✓	✓✓	OZB-A5503
	SWF 15×/∅ 17 mm	○○	○○	OZB-A5504
	SWF 20×/∅ 14 mm	○○	○○	OZB-A5505
	SWF 30×/∅ 9 mm	○○	○○	OZB-A5506
	HSWF 10×/∅ 23 mm (reticule 0,1 mm)	○	○	OZB-A5512
	SWF 15×/∅ 17 mm (reticule 0,05 mm)	○	○	OZB-A5513
	SWF 20×/∅ 14 mm (reticule 0,05 mm)	○	○	OZB-A5514
Achromatic auxiliary objectives	0,37× only in combination with a universal stand	○	○	OZB-A5611
	0,5×	○	○	OZB-A5612
	0,7×	○	○	OZB-A5613
	1,5×	○	○	OZB-A5615
	2,0×	○	○	OZB-A5616
	Soldering protection lens	○	○	OZB-A5614
C-Mount	0,3× (focus adjustable)		○	OZB-A5701
	0,5× (focus adjustable)		○	OZB-A5702
	1,0× (focus adjustable)		○	OZB-A5703
	1,0× (with micrometer) only in combination with OZB-A5703		○	OZB-A5704
	For SLR cameras (Nikon)		○	OZB-A5706
	For SLR cameras (Olympus)		○	OZB-A5707
	For SLR cameras (Canon)		○	OZB-A5708

✓ = Included with delivery ○ = Option

Functionality of our Stereomicroscope Modular System

Step 2:

Further illumination units (page 84) and a suitable protective dust cover (page 82) give you the opportunity to adapt the configuration, expansion and field of application of your ideal microscope individually to suit your own requirements.

Fiber illumination



Polarising ring light



Dust cover



Fittings and accessories for the heads for the OZO-5 microscope range (OZO 556)

Eyepiece	Magnification	Specifications - Objectives					
		Standard	Auxiliary objectives				
			1,0×	0,37×	0,5×	0,7×	1,5×
HSWF 10×	Total magnification	8× - 70×	2,96× - 25,9×	4× - 35×	5,6× - 49×	12× - 105×	16× - 140×
	Field of view mm	∅ 28,75 - 3,3	∅ 74,3 - 8,5	∅ 57,5 - 6,6	∅ 41,1 - 4,7	∅ 19,2 - 2,2	∅ 14,4 - 1,6
SWF 15×	Total magnification	12× - 105×	4,44× - 38,9×	6× - 52,5×	8,4× - 73,5×	18× - 157,5×	24× - 210×
	Field of view mm	∅ 21,25 - 2,4	∅ 57,4 - 6,6	∅ 42,5 - 4,9	∅ 30,4 - 3,5	∅ 14,2 - 1,6	∅ 10,6 - 1,2
SWF 20×	Total magnification	16× - 140×	5,92× - 51,8×	8× - 70×	11,2× - 98×	24× - 210×	32× - 280×
	Field of view mm	∅ 17,5 - 2	∅ 47,3 - 5,4	∅ 35 - 4	∅ 25 - 2,9	∅ 11,7 - 1,3	∅ 8,75 - 1
SWF 30×	Total magnification	24× - 210×	8,88× - 77,7×	12× - 105×	16,8× - 147×	36× - 315×	48× - 420×
	Field of view mm	∅ 11,25 - 1,3	∅ 30,4 - 3,5	∅ 22,5 - 2,6	∅ 16,1 - 1,8	∅ 7,5 - 0,9	∅ 5,625 - 0,6
Working distance		108 mm	275 mm	195 mm	145 mm	50 mm	35 mm

Model outfit	Model KERN	Order number
	OZO 556	
Eyepieces (30,0 mm)	HSWF 10×/∅ 23 mm	✓✓ OZB-A5503
	SWF 15×/∅ 17 mm	○ ○ OZB-A5504
	SWF 20×/∅ 14 mm	○ ○ OZB-A5505
	SWF 30×/∅ 9 mm	○ ○ OZB-A5506
	HSWF 10×/∅ 23 mm (reticule 0,1 mm)	○ OZB-A5512
	SWF 15×/∅ 17 mm (reticule 0,05 mm)	○ OZB-A5513
	SWF 20×/∅ 14 mm (reticule 0,05 mm)	○ OZB-A5514
Achromatic auxiliary objectives	0,37× only in combination with a universal stand	○ OZB-A5611
	0,5×	○ OZB-A5612
	0,7×	○ OZB-A5613
	1,5×	○ OZB-A5615
	2,0×	○ OZB-A5616
	Soldering protection lens	○ OZB-A5614
C-Mount	0,3× (focus adjustable)	OZB-A5701
	0,5× (focus adjustable)	OZB-A5702
	1,0× (focus adjustable)	OZB-A5703
	1,0× (with micrometer) only in combination with OZB-A5703	OZB-A5704
	For SLR cameras (Nikon)	OZB-A5706
	For SLR cameras (Olympus)	OZB-A5707
	For SLR cameras (Canon)	OZB-A5708

✓ = Included with delivery ○ = Option

Functionality of our Stereomicroscope Modular System

Step 3:

When using a trinocular microscope configuration, select the microscope camera (from page 85) which meets your requirements. To find the appropriate C-mount adapter, which is essential to correctly connect the camera, please see the fitting lists of the selected microscope head (from page 75).



360° rotatable microscope head	Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter	Integrated scale In the eyepiece	Battery operation Ready for battery operation. The battery type is specified for each device.
Monocular Microscope For the inspection with one eye	Fluorescence illumination for compound microscopes With 3 W LED illumination and filter	SD card For data storage	Battery operation rechargeable Prepared for a rechargeable battery operation
Binocular Microscope For the inspection with both eyes	Phase contrast unit For a higher contrast	USB 2.0 interface For data transmission	Plug-in power supply 230V/50Hz in standard version for EU. On request GB, AUS or USA version.
Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera	Darkfield condenser/unit For a higher contrast due to indirect illumination	USB 3.0 interface For data transmission	Integrated power supply unit Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.
Abbe Condenser With high numerical aperture for the concentration and the focusing of light	Polarising unit To polarise the light	WIFI data interface: For transmitting of the picture to a mobile display device	Package shipment The time required to manufacture the product internally is shown in days in the pictogram.
Halogen illumination For pictures bright and rich in contrast	Infinity system Infinity corrected optical system	HDMI digital camera For direct transmitting of the picture to a display device	Pallet shipment The time required to manufacture the product internally is shown in days in the pictogram.
LED illumination Cold, energy-saving and especially long-life illumination	Zoom magnification For stereomicroscopes	PC software To transfer the measurements from the device to a PC.	
Incident illumination For non-transparent objects	Auto-focus For automatic control of the focus level	Automatic temperature compensation For measurements between 10 °C and 30 °C	
Transmitting illumination For transparent objects	Parallel optical system For stereomicroscopes, enables fatigue-proof working	Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013	
Fluorescence illumination For stereomicroscopes			

Abbreviations

C-Mount	Adapter for the connection of a camera to a trinocular microscope	SLR camera	Single-Lens Reflex camera
FPS	Frames per second	SWF	Super Wide Field (Field number at least \varnothing 23 mm for 10 \times eyepiece)
H(S)WF	High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	W.D.	Working Distance
LWD	Long Working Distance	WF	Wide Field (Field number up to \varnothing 22 mm for 10 \times eyepiece)
N.A.	Numerical Aperture		