KERN CIB 3K-4



18 mm

Robust counting scale with large article memory, convenient operating philosophy and checkweighing display, counting resolution up to 30,000 points



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Counting scale
Product family	CIB

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	3 kg
Readability [d]	0,0002 kg
Resolution	15.000
Linearity	± 0,002 kg
Reproducibility	0,001 kg
Tare range	3 kg
Default unit	kg
Units	kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	3 kg (M1)
Stabilization time	2 s
Warm-up time	30 min
Eccentric loading at 1/3 [Max]	0,003 kg
Maximum creep (15 minutes)	800 mg
Maximum creep (30 minutes)	1,6 g

Approval	
CE mark	✓
Display	
- 1 7	
Display type	LCD

Construction	
Dimension housing (W×D×H)	350×330×120 mm
Material housing	plastic
Material weighing plate	stainless steel
Dimensions weighing surface (W×D)	315×215 mm
Display device cable length	5 m
Levelling feet adjustable	✓

Display digit height

Functions	
Number of keys for operation	34
PreTare function	✓
Tare function	manual (multi)
Counting function	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Recipe/summing level	Sum A
IP protection - load cell	IP65

Counting	
Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Counting reference weight can be entered	1
Reference quantity	n (any number of pieces)
Counting resolution (laboratory conditions)	30.000

Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0.4 A max
Input voltage device / power [Max]	12 V, 1000 mA
Plug-in power supply type	Power adapter
Supplied power supply	Battery & Power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Rechargeable battery charging time	14 h

1

KERN CIB 3K-4



Robust counting scale with large article memory, convenient operating philosophy and checkweighing display, counting resolution up to 30,000 points

Rechargeable battery operating	90 h
time - backlight on	70 11

Rechargeable battery operating 160 h time - backlight off

Battery / accumulator type Pb

Plug-in terminals Battery connection

Environmental conditions	
Humity of environment [Min]	15 %
Humity of environment [Max]	85 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C

Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	400×385×146 mm
Net weight	3,517 kg
Shipping method	Parcel service
Net weight approx.	3,6 kg
Gross weight approx.	4,2 kg
Shipping weight	4,5 kg

Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD

















OPTION

