KERN ECB 20K-2N

Plain, mobile, uncomplicated





Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Bench scale
Product family	ECB
Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	20 kg
Readability [d]	0,01 kg
Resolution	2.000
Linearity	± 0,04 kg
Reproducibility	0,01 kg
Tare range	20 kg
Default unit	kg
Units	kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	10 kg (M3)
Possible calibration points	10 kg
Stabilization time	2 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,03 kg
Maximum creep (15 minutes)	20 g
Maximum creep (30 minutes)	40 g

Approval

CE mark

DisplayDisplay typeLCDDisplay backlight✓Display digit height21 mm

1

320×300×60 mm
320×260×60 mm
Plastics
plastic
stainless steel
320×260 mm
2
selectable
3 min
manual (multi)
None
-
220 V - 240 V AC, 50 Hz
9 V, 300 mA
Power adapter
Battery
EURO UK US CH
Rchrg. battery optional - intern
10 h
30 h
30 h
6×1.5 V AA
Alkali(-Manganese)
Pad + Spring
0.17
9 V
9 V 100 h

Ambient temperature [Max]

35 °C

KERN ECB 20K-2N

Plain, mobile, uncomplicated



Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C
Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	400×375×87 mm
Net weight	2,5 kg
Shipping method	Parcel service
Net weight approx.	2,6 kg
Gross weight approx.	3,0 kg
Shipping weight	3 kg
Services (optional)	
Article number for adjustment at	0/1.040

the location of installation	961-248
Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	of 969-517

Pictograms

STANDARD



OPTION

