KERN **EMB 200-2**



Entry level laboratory balance with tremendous weighing performance



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EMB

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	200 g
Readability [d]	0,01 g
Resolution	20.000
Linearity	± 0,02 g
Reproducibility	0,01 g
Tare range	200 g
Default unit	g
Units	g dwt ozt oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 g (M1)
Possible calibration points	200 g
Stabilization time	2,5 s
Warm-up time	30 min
Eccentric loading at 1/3 [Max]	0,03 g
Maximum creep (15 minutes)	40 mg
Maximum creep (30 minutes)	80 mg

Units	dwt ozt	Rechargeable battery charging time	10 h
	OZ	Rechargeable battery operating	50 h
Adjustment options	Adjusting with external weight	time - backlight off	
3		Battery	9 V block
Recommended adjusting weight	200 g (M1)	Battery / accumulator type	Alkali(-Mar
Possible calibration points	200 g	Battery connection	Pad + Sprii
Stabilization time	2,5 s	Battery voltage	9 V
Warm-up time	30 min	Battery operating time	12 h
Eccentric loading at 1/3 [Max]	0,03 g		
Maximum creep (15 minutes)	40 mg	Environmental conditions	
Maximum creep (30 minutes)	80 mg	Humity of environment [Max]	80 %
		Ambient temperature [Min]	5 °C
Approval		Ambient temperature [Max]	35 °C
CE mark	✓	Storage temperature [Min]	-20 °C

Display	
Display type	LCD
Display screen size	58×18 mm
Display backlight	no
Display digit height	15 mm
Languages of the user interface	Symbol language

Construction	
Dimension housing (W×D×H)	170×244×39 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	plastic
Dimensions weighing surface (Ø)	105 mm

Functions	
Number of keys for operation	2
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Tare function	manual (multi)
Underfloor weighing	Hook (included in delivery)
IP protection - complete device	-

Power Supply	
Input voltage device / power [Max]	9 V, 300 mA
Plug-in power supply type	Power adapter
Supplied power supply	Battery
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Rechargeable battery optional	Rchrg. battery optional
Rechargeable battery charging time	10 h
Rechargeable battery operating time - backlight off	50 h
Battery	9 V block
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery voltage	9 V
Battery operating time	12 h

ity of environment [Max]	80 %
ient temperature [Min]	5 °C
ient temperature [Max]	35 °C
age temperature [Min]	-20 °C

KERN **EMB 200-2**



Entry level laboratory balance with tremendous weighing performance

Storage temperature [Max] 60 °C

Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	210×267×89 mm
Net weight	0,48 kg
Shipping method	Parcel service
Net weight approx.	0,50 kg
Gross weight approx.	0,70 kg
Shipping weight	1 kg

Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of	969-517

Pictograms

STANDARD



OPTION

