## KERN EMB 5.2K1



## Entry level laboratory balance with tremendous weighing performance



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EMB
Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	5200 g
Readability [d]	1 g
Resolution	5.200
Linearity	± 3 g
Reproducibility	1 g
Tare range	5200 g
Default unit	g
Units	g dwt ozt oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	5 kg (M1)
Possible calibration points	5 kg
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	3 g
Maximum creep (15 minutes)	4 g
Maximum creep (30 minutes)	8 g

1

## Approval

CE mark

Display	
Display type	LCD
Display screen size	58×18 mm
Display backlight	no
Display digit height	15 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	170×244×39 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	plastic
Dimensions weighing surface (Ø)	150 mm
Functions	
Number of keys for operation	2
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Tare function	manual (multi)
Underfloor weighing	Hook (included in delivery)
IP protection - complete device	-
Power Supply	
Input voltage device / power [Max]	9 V, 300 mA
Plug-in power supply type	Power adapter
Supplied power supply	Battery
	EURO
Plug-in power supply / adapter for	UK
countries - optional	US
	CH
Rechargeable battery optional	Rchrg. battery optional
Rechargeable battery charging time	10 h
Rechargeable battery operating time - backlight off	50 h
Battery	9 V block
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery voltage	9 V
Battery operating time	40 h
Environmental conditions	
	80 %
Environmental conditions Humity of environment [Max] Ambient temperature [Min]	80 % 5 °C

Ambient temperature [Max]

Storage temperature [Min]

35 °C

-20 °C

## KERN EMB 5.2K1



Entry level laboratory balance with tremendous weighing performance

Storage temperature [Max]	60 °C
Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	205×265×70 mm
Net weight	0,52 kg
Shipping method	Parcel service
Net weight approx.	0,55 kg
Gross weight approx.	0,70 kg
Shipping weight	0,8 kg
Services (optional)	
Article number for adjustment at the location of installation	961-248
Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	969-517
Pictograms	

STANDARD



OPTION

