## KERN **TGC 150-2S05**



0,2%

Slim pocket balance with large stainless steel weighing plate and practical tare pan

Tolerance (% of [Max])



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	Pocket balance
Product family	TGC

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	150 g
Weighing capacity [Max] (ct)	750 ct
Readability [d]	0,01 g
Readability carat [d] (ct)	0,05 ct
Resolution	15.000
Linearity	± 0,3 g
Reproducibility	0,2 g
Tare range	150 g
Default unit	g
Units	g gn dwt ozt ct oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	50 g (M2); 100 g (M2)
Possible calibration points	150 g
Stabilization time	2 s
Warm-up time	30 min
Eccentric loading at 1/3 [Max]	0,3 g
Maximum creep (15 minutes)	40 mg
Maximum creep (30 minutes)	80 mg

Approval	
CE mark	✓
Display	
Display type	LCD
Display type Display backlight	<b>√</b>
Display digit height	12 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	100×130×18 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	stainless steel
Dimensions weighing surface (Ø)	81 mm
Functions	
Number of keys for operation	4
Auto-off interval(s) in battery mode/rechargeable battery mode	4 min
Tare function	manual (multi)
IP protection - complete device	-
Power Supply	
i ower eappry	
	Battery
Supplied power supply Battery	Battery 2×CR2032
Supplied power supply Battery	-
Supplied power supply Battery Battery / accumulator type	2×CR2032 Li-Metal
Supplied power supply Battery Battery / accumulator type Battery connection	2×CR2032
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity	2×CR2032 Li-Metal Pad + Spring
Supplied power supply Battery Battery / accumulator type Battery connection	2×CR2032 Li-Metal Pad + Spring 210 mAh
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h 80 % 90 % 0 °C
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Max]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h 80 % 90 % 0 °C 40 °C
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h 80 % 90 % 0 °C
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Ambient temperature [Min] Storage temperature [Min] Storage temperature [Max]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h  80 % 90 % 0 °C 40 °C -20 °C
Supplied power supply Battery Battery / accumulator type Battery connection Battery capacity Battery operating time Battery operating time - backlight on Battery operating time - backlight off Environmental conditions Humity of environment [Min] Humity of environment [Max] Ambient temperature [Min] Storage temperature [Min]	2×CR2032 Li-Metal Pad + Spring 210 mAh 8,75 h 8,75 h 22 h  80 % 90 % 0 °C 40 °C -20 °C

1

## KERN TGC 150-2S05



Slim pocket balance with large stainless steel weighing plate and practical tare pan

Dimensions packaging (W×D×H)	100×130×16,5 mm
Net weight	0,75 kg
Shipping method	Parcel service
Net weight approx.	0,75 kg
Gross weight approx.	0,80 kg
Shipping weight	0,8 kg

Services (optional)	
Article number for adjustment at the location of installation	961-247S05
Article number for DAkkS calibration	963-127S05
Article number for certificate of conformity (verification)	969-517

## Pictograms

## **STANDARD**









**OPTION** 

