KERN TVS 20KN100-LD



Practical set for force-displacement-measurements in laboratory and industry



Category	
Brand	Sauter
Product categoriy	Test bench
Product group	Test stand set
Product family	TVS-LD
Measuring System	
Length measuring device	Length measuring device with data interface
Measurable length [Max]	21 cm
Tolerance (measured length)	0,5%
Approval	
CE mark	1
Display	
Display type	LED segments
Display type	
Diopidy type	7 segment LED
Display digit height - smallest digit	7 segment LED 9 mm
	J.
Display digit height - smallest digit	J.
Display digit height - smallest digit Construction	9 mm
Display digit height - smallest digit Construction Dimension (W×D×H) Dimensions completely mounted	9 mm 250×400×1550 mm
Display digit height - smallest digit Construction Dimension (W×D×H) Dimensions completely mounted (W×D×H)	9 mm 250×400×1550 mm 400×250×1550 mm
Display digit height - smallest digit Construction Dimension (W×D×H) Dimensions completely mounted (W×D×H) Material display housing	9 mm 250×400×1550 mm 400×250×1550 mm metal, lacquered
Display digit height - smallest digit Construction Dimension (W×D×H) Dimensions completely mounted (W×D×H) Material display housing Material housing	9 mm 250×400×1550 mm 400×250×1550 mm metal, lacquered metal, lacquered
Display digit height - smallest digit Construction Dimension (W×D×H) Dimensions completely mounted (W×D×H) Material display housing Material housing Generated force [Max]	9 mm 250×400×1550 mm 400×250×1550 mm metal, lacquered metal, lacquered 20 kN Threaded hole – 1 ×

Guide column(s) length	113,5 cm
Guide column(s) distance	215 mm
Traverse distance [Max]	210 mm
Transversal movement speed [Min]	1 mm/min
Transversal movement speed [Max]	70 mm/min
Transversal movement speed variation	1%
Functions	
Speed display	1
Repeat function	1
Pre-added and pre-reduced length	
manually adjustable	1
Length measuring - zero setting	✓
Limit switch	1
Power Supply	
Input voltage power supply / power [Max]	230 V AC, 50 Hz
	~220 V - 240 V AC; 50
Input voltage device / power [Max]	Hz
Plug-in power supply type	Built-in power supply
Plug-in power supply / adapter for	UK
countries - optional	СН
Environmental conditions	
Storage temperature [Min]	-10 °C
Storage temperature [Max]	40 °C
Packing & Shipping	
Readability force [d] (N)	2 d
Dimensions packaging (W×D×H)	600×410×1780 mm
Net weight	146 kg
Shipping method	Freight
	150 kg
Net weight approx.	0
Gross weight approx.	170 kg
Shipping weight	167 kg
Pictograms	
STANDARD	
SCALE SOFTWARE STEPPER 2 DAYS	